Tips on handling the T3[™] in use:

If the blades are deployed, put them in the undeployed position by lightly sliding the blades upward by using the outer bottom corners of each blade (caution; blades are extremely sharp) and pushing the blade forward until it stops at the tip. In the same motion, keep the blade parallel with the ferrule while pushing up and over the Spider Clip[™]. DO NOT bend the Spider Clip[™] down. If bent down, the blades will not hold properly. Because the blades are sharp, use the enclosed wrench, the eraser end of a pencil, or a similar tool for this step. For proper functioning, the slots in the ferrule must be kept clean.

Replacing the Spider Clip[™]:

Spider Clips[™] will eventually show wear after repeated use. When necessary, replace the Spider Clip[™] as follows:

- Remove the T3[™] from the arrow. Once the T3[™] has been removed from the arrow, slide off the washer, Spider Clip[™], and blades. Be sure you save your washer for re-use.
- Slide the new Spider Clip[™] over the threaded end of the ferrule, ensuring the three openings in the Spider Clip[™] line up with the three lateral grooves on the body of the ferrule.
- Replace the washer over the threaded end of the ferrule.
- Assemble the T3[™] to the arrow, using the special wrench provided, ensuring that the washer is in place between the ferrule and the insert. Be sure there is a tight fit with the Spider Clip[™] between the ferrule, washer, and arrow insert.
- Slide blades into their un-deployed position by lightly sliding blades toward nose of broadhead. In this same motion, slide blades up and over the Spider Clip[™] ensuring you do not bend or flatten the Spider Clip[™]. This allows the front of the blades to lock in place as the Spider Clips[™] hold tension on the back of the blades.
- If blades will not lock, bend the Spider Clip[™] away from ferrule and try sliding the blades back into position.

The T3[™] is ready to hunt. Practice blades are available for the T3[™].

No Spider Clip[™] is needed when using practice blades.

WARNING!!

Blades are very sharp. Use extreme care in handling.

Features of the T3[™] Package:

- As purchased, the T3[™] package contains three complete broadheads. The Spider Clips[™] are assembled to the ferrules to retain the blades.
- The package includes extra Spider Clips[™] and washers to be placed between the ferrule and the arrow insert to protect the insert if the deployed blades cut through the Spider Clip[™].
- A special wrench is also provided to protect the archer from the sharp blades during assembly.



G5 Outdoors, LLC PO Box 59 Memphis, MI 48041 P 866.456.8836 www.g5outdoors.com